

PA410

Class AB Power Amplifier

ARCAM



Features

- 4 Channel Power Amplifier
- 4 x 70W Class AB amplification (all channels driven)
- Toroidal transformer

Exceptional Power, Immersive Sound

The PA410 is a high-performance power amplifier that delivers 4 channels of efficient Class AB amplification. With an impressive 70W per channel, the PA410 is designed to offer the greatest flexibility and power without compromising on control.

Featuring the best-in-class components including a toroidal based power supply, acoustically damped chassis, and exceptionally low levels of distortion, the PA410 masters the reproduction of music with all its originality and detail for an unmatched level of sound quality and clarity.

PA410

Class AB Power Amplifier

ARCAM

Continuous power output at 0.2% THD per channel

Four channels driven, 4Ω / 8Ω, 20Hz – 20kHz	70W / 50W
---	-----------

Two channels driven, 4Ω / 8Ω, 20Hz – 20kHz	90W / 60W
--	-----------

Harmonic distortion, 80% power, 8Ω at 1kHz	0.003%
--	--------

Inputs

Input sensitivity 50W / 8Ω	600mV RMS
----------------------------	-----------

Signal/Noise ratio (A-wtd) 50W / 8Ω	105dB
-------------------------------------	-------

Input impedance	10kΩ
-----------------	------

Frequency response	20 - 20kHz +/-0.05dB
--------------------	----------------------

General

Mains voltage	110–120V or 220–240V, 50–60Hz
---------------	-------------------------------

Power consumption (maximum)	700W
-----------------------------	------

Power consumption (idle, typical)	90W (Thermal dissipation approx. 340 BTU/hour)
-----------------------------------	--

Power consumption (standby)	<0.5W
-----------------------------	-------

Dimensions W x H x D (including feet, control knob and speaker terminals)	433x325x105mm
---	---------------

Weight (net)	10kg
--------------	------

Weight (packed)	11.5kg
-----------------	--------

EAN	6925281969195
-----	---------------

